

FIBERBOND

The **Best** Filters Begin
With The **Best** Media

Multi-Wedge 85 & 95



High-Efficiency

**Multi-Wedge 85
MERV 13
and
Multi-Wedge 95
MERV 14**

**Available In
Short & Extended
Depths**

**Spor-Ax®
Antimicrobial**


**Superior
Quality & Design**

**Unmatched
Performance**

UL 900 Classified

FIBERBOND

110 Menke Road, Michigan City, IN 46360 • Phone (219) 879-4541 • Fax (219) 874-7502
Email: customer.service@fiberbond.net • www.fiberbond.net



**High-Efficiency
Multi-Wedge 85
MERV 13
&
Multi-Wedge 95
MERV 14**

**Multi-Wedge
85 & 95**

Filter Media: Non-woven composite

Flammability: UL 900 Classified

Performance: In accordance with ASHRAE 52.2 -2012 shall be MERV 13 (Multi-Wedge 85) or MERV 14 (Multi-Wedge 95)

Recommended

Final Resistance: 1.5" w.g.

Maximum Operating

Temperature: 200°F

Header: 13/16" thickness

Gasketing: Available

Face Size: Nominal less 5/ 8"

Filter Specifications

Filter shall be an extended surface, multi-pocket design

Pockets shall be *rigid and tapered in design; and formed by a heat-sealed process thus eliminating particulate migration concerns*

Media shall be a durable, multi-layer, non-woven composite that is resistant to moisture, oil mists and extreme conditions

Shall contain Spor-Ax® antimicrobial which effectively controls microbial growth on filter media

High-Efficiency Multi-Wedge Filters

Multi-Wedge filters were one of the industry's first extended surface, synthetic pocket filters and they continue to be among the best. Today's high-efficiency Multi-Wedges are engineered to offer a lower initial resistance, while maintaining all of the superior design qualities. Multi-Wedge combines the value of Spor-Ax® antimicrobial and tapered, rigid pockets - delivering a filter that maximizes service life and holds up in high moisture conditions.

Rigid, Heat-Sealed Pockets

No Particulate Migration Through Pocket Edge Seals

Lower Initial Resistance


Reduces Energy Costs

Unique, Pre-Filter Media

Extends Service Life

Spor-Ax®

Controls Microbial Growth On Filter Media



Multi-Wedge 85
MERV 13
24" x 24" x 12"
12 pockets


**Initial Resistance
0.48" w.g. at 492 fpm**

Independent test results in accordance with ASHRAE Standard 52.2-2012

Multi-Wedge 95
MERV 14
24" x 24" x 24"
8 pockets

**Initial Resistance
0.35" w.g. at 492 fpm**

Independent test results in accordance with ASHRAE Standard 52.2-2012



Multi-Wedge 85 • MERV 13 • 12" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 12 - 6	1,000 CFM	0.47"	24
16 x 24 x 12 - 8	1,135 CFM	0.47"	32
20 x 20 x 12 - 10	1,400 CFM	0.47"	37
20 x 24 x 12 - 10	1,660 CFM	0.47"	40
24 x 12 x 12 - 6	1,000 CFM	0.47"	13
24 x 20 x 12 - 12	1,660 CFM	0.47"	44.4
24 x 24 x 12 - 12	2,000 CFM	0.47"	48

Multi-Wedge 95 • MERV 14 • 12" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 12 - 6	1,000 CFM	0.49"	24
16 x 24 x 12 - 8	1,135 CFM	0.49"	32
20 x 20 x 12 - 10	1,400 CFM	0.49"	37
20 x 24 x 12 - 10	1,660 CFM	0.49"	40
24 x 12 x 12 - 6	1,000 CFM	0.49"	13
24 x 20 x 12 - 12	1,660 CFM	0.49"	44.4
24 x 24 x 12 - 12	2,000 CFM	0.49"	48

Multi-Wedge 85 • MERV 13 • 24" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 24 - 3	1,000 CFM	0.42"	23.6
12 x 24 x 24 - 4	1,000 CFM	0.36"	31.5
16 x 24 x 24 - 5	1,135 CFM	0.36"	39.4
20 x 20 x 24 - 5	1,400 CFM	0.42"	34.6
20 x 20 x 24 - 6	1,400 CFM	0.36"	47
20 x 24 x 24 - 5	1,660 CFM	0.42"	39.4
20 x 24 x 24 - 6	1,660 CFM	0.36"	47
24 x 12 x 24 - 5	1,000 CFM	0.42"	21.7
24 x 12 x 24 - 6	1,000 CFM	0.36"	26
24 x 20 x 24 - 6	1,660 CFM	0.42"	41.5
24 x 20 x 24 - 8	1,660 CFM	0.36"	55.3
24 x 24 x 24 - 6	2,000 CFM	0.42"	47
24 x 24 x 24 - 8	2,000 CFM	0.36"	63

Multi-Wedge 85 • MERV 13 • 30" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 30 - 4	1,000 CFM	0.36"	39
20 x 24 x 30 - 6	1,660 CFM	0.36"	59
24 x 12 x 30 - 6	1,000 CFM	0.36"	32.5
24 x 24 x 30 - 8	2,000 CFM	0.36"	78.5

Contact Fiber Bond for availability of sizes not shown.

MERV 9 & MERV 11 Multi-Wedge Filters Also Available

FIBERBOND

110 Menke Road • Michigan City, Indiana 46360
(219) 879-4541 • Fax (219) 874-7502
Email: customer.service@fiberbond.net

Fiber Bond has a policy of continuous product research and improvement and reserves the right to alter design and specifications without notice.

Multi-Wedge 95 • MERV 14 • 15" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 15 - 6	1,000 CFM	0.46"	30
16 x 24 x 15 - 8	1,135 CFM	0.46"	40
20 x 20 x 15 - 10	1,400 CFM	0.46"	45.8
20 x 24 x 15 - 10	1,660 CFM	0.46"	50
24 x 12 x 15 - 6	1,000 CFM	0.46"	19
24 x 20 x 15 - 12	1,660 CFM	0.46"	56.4
24 x 24 x 15 - 12	2,000 CFM	0.46"	60

Multi-Wedge 95 • MERV 14 • 24" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 24 - 3	1,000 CFM	0.44"	23.6
12 x 24 x 24 - 4	1,000 CFM	0.38"	31.5
20 x 20 x 24 - 5	1,400 CFM	0.44"	34.6
20 x 20 x 24 - 6	1,400 CFM	0.38"	47
20 x 24 x 24 - 5	1,660 CFM	0.44"	39
20 x 24 x 24 - 6	1,660 CFM	0.38"	47
24 x 12 x 24 - 5	1,000 CFM	0.44"	21.7
24 x 12 x 24 - 6	1,000 CFM	0.38"	26
24 x 20 x 24 - 6	1,660 CFM	0.44"	41.5
24 x 20 x 24 - 8	1,660 CFM	0.38"	55.3
24 x 24 x 24 - 6	2,000 CFM	0.44"	47
24 x 24 x 24 - 8	2,000 CFM	0.38"	63

Multi-Wedge 95 • MERV 14 • 30" Depth

Nominal Size w x h x d -pockets	Air Flow CFM	Resistance @ 500 fpm	Media (sq ft)
12 x 24 x 30 - 4	1,000 CFM	0.38"	39
20 x 24 x 30 - 6	1,660 CFM	0.38"	59
24 x 12 x 30 - 6	1,000 CFM	0.38"	32.5
24 x 24 x 30 - 8	2,000 CFM	0.38"	78.5

Performance tolerances conform to Section 7.4 of ARI Standard 850 - 2004.

September 2013